

# Performer® Series

Economical, electronic pumps  
and consumer-friendly.

Gilbarco® has pioneered some of the world's most highly sophisticated electronic dispenser technology, and now brings you the value of this technology, economically offered in the Performer™ series of pumps and dispensers. Inside, the Performer series includes the same highly reliable electronic components and hydraulic assemblies used in Gilbarco's Legacy® series and The Advantage® series of pumps and dispensers. The Performer series is also specifically designed to bring you the benefits of Gilbarco technology at the lowest possible price. The Performer series provides an electronic image, electronic communication with other devices, and low cost of ownership. Gilbarco manufactures the unit in black or white, allowing plenty of room for customer-supplied graphics. As with all Gilbarco products, you benefit from the sales and service support of Gilbarco's worldwide network of professional distributors.



## Console compatibility

By adding optional hydraulic valves, the Performer series can interface with Transac® System 1000™ pump controller, PAM™ Pump Access Module, or Gilbarco's G-SITE® management system for indoor programming, control and management of the fuel island.

# Models and Specifications

Model Number	Unit Type	Products	Hoses	Pump/Dispenser	Motor	Standard Weight (kg)	Shipping Shipping Volume
JE1000	Standard	1	1	Pump	3/4 HP	167.4 kg (372 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JE1100	Standard	1	2	Pump	3/4 HP	186.8 kg (415 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JE1200	Standard	2	2	Pump	3/4 HP	216.9 kg (482 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JE1300	High	1	1	Pump	3/4 HP	159.8 kg (355 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JE1500	High	2	2	Pump	3/4 HP	247.5 kg (550 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JEA000	Standard	1	1	Dispenser	N/A	92.3 kg (205 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JEA100	Standard	1	2	Dispenser	N/A	114.8 kg (255 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JEA200	Standard	2	2	Dispenser	N/A	147.6 kg (328 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JEA300	High	1	1	Dispenser	N/A	114.8 kg (255 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JEA400	High	1	2	Dispenser	N/A	128.3 kg (285 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H
JEA500	High	2	2	Dispenser	N/A	141.8 kg (315 lbs.)	91.4 cm (36")W x 55.9 cm (22")D x 165.1 cm (65")H

## Standard features

- Mechanical totalizers display the volume dispensed for each meter (99,999.99)
- 3/4 HP, 220V or 230V, 50Hz. or 60Hz., single-phase motor
- Hose hooks
- Easy-to-read 1.52 cm (0.6") LCD displays with choice of background colors
- Manager keypad for programming
- Combination rotary vane type pumping units with six durable blades and integral cast aluminum air separator on self-contained pump models
- Four-piston positive displacement meters accurate within 0.26%
- Gilbarco 10-micron high density spin-on filters with back-up strainers
- Unit dimensions: 686mm W x 1m 458mm H x 411mm D (27.44"W x 58.35"H x 16.44"D)
- Painted lower doors and head, stainless steel side sheathing

## Options

- Hoses
- 2.54cm (1") LCD displays with choice of background colors
- Customer Programmable Preset customer or attendant preset for any money or volume amount
- Incremental Preset allows customer or attendant to accumulate money or volume preset by adding 10, 5, and 1 values
- Combination rotary internal gear type pumping unit and air separator for more efficient and quieter fuel delivery
- Higher horsepower motors for faster flow rates
- Side-mounted hose retrievers
- High Retriever option, to discreetly keep hoses up to 5 meters long off the ground, accommodates hoses 16mm, 19mm, and 25mm diameter (5/8", 3/4", and 1" diameter)



- Flexmast mounting hardware
- Hydraulic valves for console applications
- Push To Start or Push To Stop option (when preset option is also added)
- Stainless steel lower doors

