

TLS-450 PLUS

Proven Wet Stock Management

- > Proven Protection
- > Proven Precision
- > Proven Profit
- > Proven Partner



Keeping the World Moving



**GILBARCO
VEEDER-ROOT**

TLS-450 PLUS Specification Sheet

8600 & 8601 Series Consoles

Standard Features

WVGA LCD colour touch screen with user-friendly graphic display	✓
Internal 5 amp relays, 120/240 VAC or 30 Vdc	1
Maximum number of universal probe and/or sensor inputs	256 ¹
Maximum number of probes	32
Web-enabled: view and control from web or smart phone browsers	✓

¹=With TLS-XB

Communications

Configurable RS-232/RS-485 serial ports	5 ¹
Ethernet port(s)	3
Ethernet network(s)	2
USB ports (external/internal)	2/2

¹=Up to

System Specifications

Multipoint tank chart, supports up to 5,000 unique points	✓
Network printer support via Ethernet	✓
Approximate external dimensions (centimetres)	46 x 28 x 22

Operational Features

Custom alarms for unique labelling or on-site instruction	✓
Workflow wizard for streamlined setup	✓
Up to three years of history available	✓
Software upgrade through USB	✓
Remote software download capability via Ethernet ¹	✓

¹=Available on version 5B or higher

Additional Functionality When Combined with Appropriate Equipment and/or Software

AccuChart tank calibration including selectable calibration range and data sufficiency tracking	Optional
Digital Pressurised Line Leak Detection (DPLLD) – 0.38 LPH annual, 0.76 LPH monthly & 11.35 LPH hourly testing	Optional
In-Tank Static Leak Detection (SLD) – 0.38 LPH annual and 0.76 LPH monthly testing	✓
Continuous Statistical Leak Detection (CSLD) – 0.76 LPH for single and manifolded tanks	Optional
Mag-FLEX tall tank AST monitoring	✓

Keeping the World Moving

Sales 1300 131 867
Sales.oz@Gilbarco.com
www.gilbarco.com.au

