

TLS4 & TLS4B PLUS

Proven Wet Stock Management

- > Proven Protection
- > Proven Precision
- > Proven Profit
- > Proven Partner



Keeping the World Moving



TLS4 & TLS4B PLUS Specification Sheet

8600 & 8601 Series Consoles

Standard Features	TLS4	TLS4B
WVGA LCD colour touch screen with user-friendly graphic display	✓	✓
Internal 5 amp relays, 120/240 VAC or 30 Vdc	2	2
One internal universal low voltage input, 12 Vdc (contact closure sense)	✓	✓
Maximum number of universal probe and/or sensor inputs	12	6
Maximum number of probes	12	6
Web-enabled: view and control from web or smart phone browsers	✓	✓

Communications	TLS4	TLS4B
Configurable RS-232/RS-485 serial ports	2	2
Ethernet port(s)	3	1
Ethernet network(s)	2	1
USB ports (external/internal)	2/0	2/0

System Specifications	TLS4	TLS4B
Multipoint tank chart, supports up to 5,000 unique points	✓	✓
Network printer support via Ethernet	✓	✓
Approximate external dimensions (centimetres)	33 x 20 x 9	33 x 20 x 9

Operational Features	TLS4	TLS4B
Custom alarms for unique labelling or on-site instruction	✓	✓
Workflow wizard for streamlined setup	✓	✓
Up to three years of history available	✓	✓
Software upgrade through USB	✓	✓
Remote software download capability via Ethernet ¹	✓	✓

¹=Available on version 5B or higher

Additional Functionality <small>When Combined with Appropriate Equipment and/or Software</small>	TLS4	TLS4B
AccuChart tank calibration including selectable calibration range and data sufficiency tracking	Optional	Optional ¹
In-Tank Static Leak Detection (SLD) – 0.38 LPH annual and 0.76 LPH monthly testing	✓	Optional
Continuous Statistical Leak Detection (CSLD) – 0.76 LPH for single and manifolded tanks	Optional	
Mag-FLEX tall tank AST monitoring	✓	✓

¹=Available on version 6B or higher

Keeping the World Moving

Sales 1300 131 867
Sales.oz@Gilbarco.com
www.gilbarco.com.au

