



Feature	Description	9853	9840	9850	9820	9872	9153	9140	9120	215/216Q
Approvals	cUL and UL listed, NCWM, Measurement Canada	S	S	S	S	S	S	S	S	S
Working Pressure	50 psi maximum	S	S	S	S	S	S	S	S	S
Unit of Measure	Gallons (liters optional)	S	S	S	S	S	S	S	S	S
Motor/Voltages	1 HP continuous duty motor 115V/60HZ — (230V/50HZ is optional)	S	S	S	S	S	S	S	S	
	1½ HP continuous duty motor 115V/60HZ — (230V/50HZ is optional)			S		0				
Pumps	¾ HP continuous duty motor 380V/50HZ/3-Phase	0	0		0		0	0	0	
	10 vane rotary pump with integrated air separator	S	S		S		S	S	S	
	High speed rotary vane pump with integrated air separator			S						
Solenoid Valve	1" or 1½" solenoid valve for slow-down preset operation (PP)	1"	1½"	1½"	1"	1"	1"	1½"	1"	
Filters	Integrated internal spin-on filter (F) — external spin-on type optional on all models	S	S		S	E85	S	S	S	
Discharge	1" or 1¼" NPT black iron	1"	1¼"	1¼"	1"	¾ NPT	1"	1¼"	1"	1", 215 1¼", 216
Satellite Piping	Dispensers only (S)	0	0	0			0	0		
Inlet	1½" or 2" NPT inlet	1½"	2"	2"	1½"	1½"	1½"	2"	1½"	1½"
Housing	Painted G90 galvanized steel	13 GA	13 GA	13 GA	11 GA		13 GA	13 GA	11 GA	12 GA
Panels	Lockable removable panels - painted 20 gauge or 16 gauge G60	20	20	20	16	20	20	20	16	16
	Lockable removable panels - Stainless steel 22 gauge Kooline	0	0	0		0	0	0		
	Lockable removable panels - Stainless steel 20 gauge Type 304					S				0
Sheathing	Painted replaceable sheathing - G60 galvanized	22	22	22	16	22	22	22	16	16
	All panels stainless steel Type 304 — stainless steel - Kooline (optional)	22	22	22		22	22	22		20
Computer/Register	Electronic Register: Volume only display. Electronic totalizer displayed on LCD by magnetic switch.	S	S	S		S				
	Mechanical Register: VR10 - Volume only, includes integrated totalizer and power reset						S	S		
Electronic Display	Mechanical Register: Four-wheel gallons/liters only, displays up to 999.9. Includes 7-digit totalizer and power reset								S	
	Volume only front display. 1" backlit LCD. Maximum 999.000 gallons or 9999.00 liters.	S	S	S	S					
Interface Options	Pulser: (10.1 or 100.1 volume) for key or card systems (CC or CX)						0	0	0	
	Card System Interface: RS-485 interface for direct connection to Gasboy CFN System, Islander, or TopKAT	0	0	0	0	0				
	Card System Interface - pulse output: selectable pulse/gallon outputs for interfacing with fuel control systems.	0	0	0	0	0				
Brand Panel Lighting	DC conduit and junction box (D)	S	S	S						
	Keytrol (EK)						0	0		
	Lighted brand panel (L)	0	0	0		0	0	0		
Totalizers	Non-settable Electro-Mechanical	0	0	0		0				
	Non-settable Mechanical				0				S	
Nozzle Positions	Side Mount	S	S	S		S	S	S		S
	Front Mount	0	0	0	S	0			S	0
Hose Retractors	Internal hose retractor (I)	0	0				0	0		
	High hose retractor: post-mounted retractor with enclosed spring return reel.	0	0	0	0		0	0	0	0
AST Applications	Pressure Regulating Valve Model 52A (9048577) — suction pumps only	0			0		0		0	
	9850 Above Ground Tank Kit — suction pumps only			0						
Warranty	Parts and labor - 12 month	S	S	S	S	S	S	S	S	S
	Parts and labor - 24 month	0	0	0	0	0	0	0	0	0
Miscellaneous	ATC (Canada only)	0	0	0						
	Hand crank (K)						0	0		
	Battery backup	0	0	0		0				
	Vapor Recovery: Balanced vapor recovery system	0			0				0	0
	Vapor Recovery: Healy Universal Kit compatible	0					0			
Hose: ¾" or 1" standard or Vapor Recovery (specify length)	0	0	0	0	0	0	0	0	0	
Automatic nozzles, breakaway valves, and swivels	0	0	0	0	0	0	0	0	0	

S = Standard, 0 = Optional



Atlas® pumps & dispensers for fleet operations

Choose from the industry's leading range of pump and dispenser models, with features and options designed specifically to meet the unique needs of fleet operators.

High models provide fast fueling for large vehicles. Satellite dispensers allow simultaneous fueling of saddle tanks to reduce fueling time.

The Gasboy® Atlas series is rugged, durable, reliable and perfectly suited for the tough fleet fueling environment. Electronic and mechanical choices are lit for unattended applications. High flow, Super High Flow, and Ultra

Gasboy Atlas pumps and dispensers are compatible with a full range of Gasboy Fleet Management Systems to help you track and manage your fleet better. From the most simple system to the most comprehensive one, Gasboy offers turnkey solutions to simplify your operation.

Gilbarco Veeder-Root Middle East & Africa
 Arjaan Tower, 9th Floor
 Dubai Media City, P.O Box 71569
 Dubai, UAE
 Tel: +971 4465050
 Email: salesmea@gilbarco.com
 www.gilbarco.com/mea

Gilbarco Veeder-Root Asia Pte Ltd
 750A Chai Chee Road
 #07-02 Technopark@Chai Chee
 Singapore, 469001
 Tel: +65 6448 7626
 Email: salessea@gilbarco.com
 www.gilbarco.com/sea



Mechanical pumps and dispensers

Super High Flow (up to 40 gpm/151 lpm)*

Model Number	Type	Hoses	Products	Motors	Meters
9140K	Pump	Single	1	(2) 1 hp c.d.	(2) Gilbarco CFT
9140KX	Dispenser	Single	1	n/a	(2) Gilbarco CFT

High Flow (up to 22 gpm/83 lpm)*

Model Number	Type	Hoses	Products	Motors	Meters
9153K	Pump	Single	1	(1) 1 hp c.d.	Gilbarco CFT
9152KTW1	Pump	Twin	1	(1) 1 hp c.d.	Gilbarco CFT
9153KTW1M	Pump	Twin	1	(2) 1 hp c.d.	Gilbarco CFT
9153KTW2	Pump	Twin	2	(2) 1 hp c.d.	Gilbarco CFT
9153KX	Dispenser	Single	1	n/a	Gilbarco CFT
9153KXTW1	Dispenser	Twin	1	n/a	Gilbarco CFT
9153KXTW2	Dispenser	Twin	2	n/a	Gilbarco CFT



Satellite dispensers

Model Number	Works With	Hoses	Products	GPM(LPM)*	Motors	Meters
215Q	9153KX 9853KX	Single	1	Up to 21	n/a	n/a
215Q-Z		Single	1	Up to 21	n/a	n/a
215QTW-Z		Twin	1	Up to 21	n/a	n/a
216Q	9850KX 9840KX 9140KX	Single	1	Up to 40	n/a	n/a
216Q-Z		Single	1	Up to 40	na/	n/a
216QTW-Z		Twin	1	Up to 40	n/a	n/a

Ultra High Flow (up to 50 gpm/189 lpm)*

Model Number	Type	Hoses	Products	Motors	Meters
9850K	Pump	Single	1	(1) 1½ hp c.d.	Liquid Controls
9850KTW3	Pump	Combo	1	(1) 1½ hp c.d.	Liquid Controls
9850KX	Dispenser	Single	1	n/a	Liquid Controls
9850KXTW1	Dispenser	Twin	1	n/a	Liquid Controls
9850KXTW2	Dispenser	Twin	2	n/a	Liquid Controls
9850KXTW2	Dispenser	Combo	1	n/a	Liquid Controls

Super High Flow (up to 40 gpm/151 lpm)*

Model Number	Type	Hoses	Products	Motors	Meters
9840K	Pump	Single	1	(2) 1 hp c.d.	(2) Gilbarco CFT
9840KX	Dispenser	Single	1	n/a	(2) Gilbarco CFT

High Flow (up to 22 gpm/83 lpm)*

Model Number	Type	Hoses	Products	Motors	Meters
9853K	Pump	Single	1	(1) 1 hp c.d.	Gilbarco CFT
9852KTW1	Pump	Twin	1	(1) 1 hp c.d.	Gilbarco CFT
9853KTW1M	Pump	Twin	1	(2) 1 hp c.d.	Gilbarco CFT
9853KTW2	Pump	Twin	2	(2) 1 hp c.d.	Gilbarco CFT
9853KX	Dispenser	Single	1	n/a	Gilbarco CFT
9853KXTW1	Dispenser	Twin	1	n/a	Gilbarco CFT

E85 Electronic Dispensers

Model Number	Type	Hoses	Products	Nozzle Position	Meters
9872KX F	Dispenser	Single	1	Side	(1) C+
9872KX FZ	Dispenser	Single	1	Front	(1) C+
9872KXTW1 Z	Dispenser	Twin	1	Front	(2) C+



Electronic pumps and dispensers

