



## Legacy<sup>®</sup> Series

Gilbarco Veeder-Root's Legacy electronics pumps and dispensers are the perfect solution for retailers who just need the basics. This series offers a rugged, dependable, and field proven way to offer your customers what they want. Legacy dispensers are small enough to place away from your main forecourt to offer a fuel like kerosene. Truck stop operators find Legacy Ultra-Hi and High Flow masters, satellites, and combo models perfect for simultaneous fueling of large truck saddle tanks. With Legacy, get simple solutions for basic fueling from the industry leader.

## Simple solutions for basic fueling. - Legacy® Series

Legacy<sup>®</sup> Electronic Models







Model	Flow Rate	Products	Hoses	Pump/Dispenser	Standard Motor	Shipping Weight (kg)	Shipping Volume (m3)
JH1000	Standard	1	1	Pump	3⁄4 HP	169	1.1
JH1100	Standard	1	2	Pump	3⁄4 HP	190	1.1
JH1200	Standard	2	2	Pump	3⁄4 HP	219	1.1
JH1300	High	1	1	Pump	3⁄4 HP	160	1.1
JH1500	High	2	2	Pump	3⁄4 HP	250	1.1
JHA000	Standard	1	1	Dispenser	n/a	95	1.1
JHA100	Standard	1	2	Dispenser	n/a	115	1.1
JHA200	Standard	2	2	Dispenser	n/a	170	1.1
JHA300	High	1	1	Dispenser	n/a	115	1.1
JHA400	High	1	2	Dispenser	n/a	130	1.1
JHA500	High	2	2	Dispenser	n/a	140	1.1

## Legacy® Ultra-Hi and High Flow, Master, Satellite, and Combo Models

Model	Flow Rate	Products	Hoses	Pump/Dispenser	Standard Motor	Shipping Weight (kg)	Shipping Volume (m3)
JHB310	High	1	1	Master Dispenser	n/a	169	1.1
JHB410	High	1	2	Master Dispenser	n/a	190	1.1
JHB510	High	2	2	Master Dispenser	n/a	219	1.1
JHB600	Ultra-Hi	1	1	Master Dispenser	n/a	160	1.1
JHB800	Ultra-Hi	2	2	Master Dispenser	n/a	250	1.1
JHC310	High	1	1	Satellite Dispenser	n/a	95	1.1
JHC510	High	2	2	Satellite Dispenser	n/a	115	1.1
JHC600	Ultra-Hi	1	1	Satellite Dispenser	n/a	170	1.1
JHC800	Ultra-Hi	2	2	Satellite Dispenser	n/a	115	1.1
JHD510	High	2	2	Master/Satellite Dispenser	n/a	130	1.1
JHD800	Ultra-Hi	2	2	Master/Satellite Dispenser	n/a	140	1.1

Gilbarco's Encore® Ultra-Hi Flow masters, satellites, and combos are also available with integrated pay-at-the-pump. Refer to Gilbarco brochure P-2321D for more information.

Standard Features:
> Measurement in U.S. gallons, liters, or Imperial gallons
> Gilbarco "C" meter for standard and high flow models
> Solid state pulsers
> Gerotor gear pump with passive air separation system
3/4 hp motor (Self-Contained models only)
> Hoses and nozzles sold seperately
> 27-inch locking lower access doors, painted/decal
> Electro-mechanical totalizers
> Lighted face plates
> Liquid Crystal Displays (LCD) with orange backlighting
> Hose retriever

S Lane-oriented putdowns (Ultra-Hi, Master, & Satellite models)
 Island-oriented putdowns (standard flow and high flow models)

- Standard Features: (cont)

  Liquid Controls<sup>®</sup> meter for Ultra-Hi models
  - > Programmable for 6 digit money (xxxx.xx)
- > Four-piston positive displacement meters (excluding Ultra-Hi)
- > Electronic calibration

Options:
> Stainless steel lower doors
> Incremental preset
> Nozzle-activated reset (export only)
> Satellite-on light
> Visual discharge indicators
> Hoses: 3.64m x 1.9cm (12' x ¾") for standard flow 3.64m x 2.5cm (12' x 1") for high flow rate units

Approvals:
>  cUL and UL listed
> Conforms with NIST Handbook 44
> NTEP Certification No. 94-027

Ma	otors:
>	¾ HP 120V AC (+10%), 60Hz, 1 Phase
>	<sup>3</sup> ⁄4 HP 220V AC (+10%), 60Hz, 1 Phase
>	¾ HP 115/220 - 230V AC (+10%), 50Hz, 1 Phase
>	¾ HP 380V AC (+10%), 50/60Hz, 3 Phase
>	¾ HP 220/380V AC (+10%), 50/60Hz
	* 3 Phase available, not UL approved

Gilbarco Veeder-Root Asia Pte Ltd | 750A Chai Chee Road | #07-02 Technopark@Chai Chee | Singapore, 469001 | Tel: +65 6448 7626 | Email: salessea@gilbarco.com | www.gilbarco.com/sea